



PRESSURE SWITCHES

PISTON TYPE



Part No. 201257
Pressure 2MPa
(20 bar) (280 psi.)

Part No. 201256
Pressure 4MPa
(40 bar) (570 psi.)

Characteristics:
Change-over contact: 15A - 220V AC
0.25A - 250V DC
Max. safe pressure: 10MPa (100 bar) (1420 psi.)
Differential: 0,5MPa (5 bar) (71 psi.)
Working temperature: -20°C to +70°C (-4°F to +158°F)
Protection: IP54
Weight: 0,4 kg. (.88 lb.)
Connection: 1/8" BSP (1/8" NPT)
with seat for ø4 mm. tube

Part No. 54021 -Adjustable from 4MPa to 16MPa (40 to 160 bar) (570 to 2280 psi.)
Supplied complete with fixing bracket.

Part No. 54025 -Adjustable from 0,5MPa to 3MPa (5 to 30 bar) (71 to 430 psi.)
Supplied complete with fixing bracket.

Part No. 1124300 -Adjustable from 4MPa to 16MPa (40 to 160 bar) (570 to 2280 psi.)
Supplied complete with fixing bracket and air purge fitting.



Characteristics:
Change-over contact: 10A - 110V AC - 0.6A - 110V DC
Protection: IP54
Max. safe pressure: 24MPa (240 bar) (3400 psi.)
Working temperature: -20°C to +70°C (-4°F to +158°F)
Connection: 5/16-24 NF with seat for ø4 mm. tube

Web site:
<http://www.dropsa.com>

E-mail:
sales@dropsa.com

WK 26/87
C1020PE

ITALY
Dropsa SpA
t.(+39) 02-250791
f.(+39) 02-25079767

SPAIN
Polydrop, S.A.
t.(+34) 93-260-22-50
f.(+34) 93-260-22-51

U.S.A.
Dropsa Corporation
t.(+1) 586-566-1540
f.(+1) 586-566-1541

U.K.
Dropsa (UK) Ltd
t.(+44) 01784-431177
f.(+44) 01784-438598

BRAZIL
Dropsa
t.(+55) 011-563-10007
f.(+55) 011-563-19408

GERMANY
Dropsa GmbH
t.(+49) 0211-394-011
f.(+49) 0211-394-013

AUSTRALIA
Dropsa Australia Ltd.
t.(+61) 2-9938-6644
f.(+61) 2-9938-6611

FRANCE
Dropsa France
t.(+33) 01-3993-0033
f.(+33) 01-3986-2636